

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir stump, 26 ins. diam., bears S. 54° E., 27 lks. dist., with illegible scribe marks visible on partially open blaze.

A cedar, 18 ins. diam., bears N. 22° W., 33 lks. dist., with scribe marks BT visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
¼
S 11 | S 12
1974

from which new bearing trees

A cedar, 22 ins. diam., bears S. 77° E., 28½ lks. dist., mkd. ¼ S12 BT.

A cedar, 14 ins. diam., bears N. 57½° W., 143½ lks. dist., mkd. ¼ S11 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 23 and 26, determined at record bearing and distance from the remains of the original bearing trees:

A sawed fir stump, 20 ins. diam., bears S. 24° E., 47 lks. dist., with scribe marks BT visible on lower portion of opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
¼ S 23
 S 26
1974

from which new bearing trees

A live oak, 11 ins. diam., bears N. 9¼° W., 106 lks. dist., mkd. ¼ S23 BT.

A fir, 37 ins. diam., bears S. 3° W., 115 lks. dist., mkd. ¼ S26 BT.

The ¼ sec. cor. of secs. 14 and 23, monumented with the original basalt stone, 16 x 10 x 8 ins., firmly set 11 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A sawed white fir stump, 22 ins. diam., bears N. 23° W., 44 lks. dist., with scribe marks BT visible on detached portion of opened blaze.

A fir, 20 ins. diam., bears S. 50° E., 34 lks. dist., with healed blaze.