

Remonumentation of Certain Original Corner Points, 15631
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 33 S R 5 W
 $\frac{1}{4}$ S 14
S 23
1974

from which a new bearing tree

A fir, 7 ins. diam., bears N. 74° W., 86 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented with the original granite stone, 16 x 8 x 5 ins., firmly set 11 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with an iron rod driven alongside, $\frac{5}{8}$ in. diam., firmly set, protruding 12 ins. above ground, from which the original bearing trees:

A fir, 40 ins. diam., bears N. $27\frac{1}{2}^\circ$ E., 53 lks. dist., with healed original blaze. This tree was rescribed by the County Surveyor, in 1930, with scribe marks $\frac{1}{4}$ S2 CS BT visible on bark.

A fir, 36 ins. diam., bears S. 41° W., 44 lks. dist., with healed blaze. This tree was rescribed by the County Surveyor, in 1930, with scribe marks 4S CS visible on partially open blaze.

and a bearing tree mkd. by the County Surveyor, in 1967

A fir, 6 ins. diam., bears N. 52° E., 30 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
 $\frac{1}{4}$ S 2
S 11
1974

Deposit corner stone and reset iron rod alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with the original slate stone, 18 x 12 x 6 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees:

A fir, 32 ins. diam., bears N. $30\frac{1}{2}^\circ$ E., 149 lks. dist., with healed blaze.

A sugar pine, 51 ins. diam., bears S. $36\frac{1}{2}^\circ$ W., 115 lks. dist., with healed blaze. (Record, 112 lks. to face)