

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$
S 3 | S 2
1974

from which a new bearing tree

A fir, 18 ins. diam., bears N. 60° E., $61\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S2 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, perpetuated and recorded by Herbert R. Jones, Registered Engineer No. 2451, in 1963, monumented with a cedar post, 4 ins. square, firmly set, protruding 4 ft. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 26 ins. diam., bears N. 19° W., 12 lks. dist., with reverse scribe mark T visible on detached portion of lower blaze.

and the remains of bearing trees mkd. by Jones

A sawed fir stump, 24 ins. diam., bears N. 38° W., 39 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

A sawed fir stump, 18 ins. diam., bears S. $23\frac{1}{2}^\circ$ W., 129 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$
S 27
S 34
1974

No suitable trees available within limits.

Deposit cedar post alongside iron post.

Corner is located on a steep W. slope, in a clear cut, 30 lks. west of a dirt road, 20 lks. wide, bears N. 10° E. and S. 10° W.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, determined at record bearing and distance from the remains of the original bearing tree:

A decayed pine stump, size indeterminate, bears S. $18\frac{1}{2}^\circ$ W., 86 lks. dist., with scribe mark 1 visible on open and burned blaze.

At the corner point

Jones

Joseph Jones