

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

15633

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$$\frac{1}{4} \begin{array}{l} S 22 \\ S 27 \end{array}$$

1974

from which new bearing trees

A ponderosa pine, 14 ins. diam., bears N. 31° W., 42 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

A cedar, 11 ins. diam., bears S. 8° E., $15\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S27 BT.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with the original slate stone, 12 x 10 x 5 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees:

A black oak, 18 ins. diam., bears N. $2\frac{1}{2}^\circ$ E., 99 lks. dist., with healed double blaze.

A ponderosa pine, 25 ins. diam., bears S. $75\frac{3}{4}^\circ$ W., 103 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$$\frac{1}{4} \begin{array}{l} S 20 \\ S 21 \end{array}$$

1974

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. $7\frac{1}{2}^\circ$ E., 66 lks. dist., with a down fir alongside, 27 ins. diam., with scribe marks $\frac{1}{4}$ S visible on partially open blaze.

A root hole, bears S. 54° W., 47 lks. dist.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$$\frac{1}{4} \begin{array}{l} S 5 \\ S 4 \end{array}$$

1974

from which new bearing trees

A fir, 36 ins. diam., bears S. 67° E., $82\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT.

A fir, 16 ins. diam., bears S. $26\frac{1}{2}^\circ$ W., 35 lks. dist., mkd. $\frac{1}{4}$ S5 BT.