

Remonumentation of Certain Original Corner Points, **15634**
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, determined at record distance from the original bearing trees:

A cedar, 30 ins. diam., bears S. 59° E., 46 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears S. 62° W., 16 lks. dist., with healed blaze. (Record, S. 67° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$ $\frac{S 8}{S 17}$

1974

No suitable trees available in sec. 8.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 30 ins. diam., bears S. 15° E., 61 lks. dist., with healed blaze.

A fir, 36 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ W., 38 lks. dist., with scribe marks $\frac{1}{4}$ visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$ S 7 | S 8

1974

from which new bearing trees

A fir, 7 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 57 lks. dist. mkd. $\frac{1}{4}$ S8 BT.

A fir, 32 ins. diam., bears S. 40° W., $26\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S7 BT.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, determined at record bearing and distance from the remains of the original bearing tree:

A black oak, 26 ins. diam., bears N. 29° E., 37 lks. dist., with scribe marks 4 BT visible in negative on partially opened and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$ $\frac{S 5}{S 8}$

1974

Joseph L. Linn
*1/2 NW
Co.
Dove Co
Linn*