

15636

T. 24 S., R. 1 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the subdivision of section 14, township 24 south, range 1 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey, is as follows:

The subdivisional lines were surveyed by Carl S. Nicklin and Winfield S. Chapman, in 1896.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 1, 1974, for Group Number 853, Oregon.

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the survey, identified corners were remonumented in their original positions. The line surveyed was fully blazed and measured twice to preclude error.

The geographic position of the  $\frac{1}{4}$  section corner of sections 14 and 23, as scaled from the Mace Mountain, Oregon, quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude  $43^{\circ} 28.9' N.$  Longitude  $122^{\circ} 46.1' W.$

The mean magnetic declination is  $20^{\circ} E.$

Subdivision of Section 14, T. 24 S., R. 1 W.,  
Willamette Meridian, Oregon

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, perpetuated and recorded by James W. Byron, County Surveyor, in 1966, monumented with an iron pipe,  $1\frac{1}{2}$  ins. diam., firmly set, protruding 16 ins. above ground, with brass cap mkd.

T 24 S  
 $\frac{1}{4}$   $\frac{S 14}{S 23}$   
R 1 W  
1966

from which the remains of the original bearing trees

A cedar, 34 ins. diam., bears N.  $5^{\circ} W.$ , 55 lks. dist., with scribe marks S T visible on opened blaze.

and bearing trees mkd. by Byron

A chinquapin, 8 ins. diam., bears S.  $83^{\circ} W.$ , 28 lks. dist., with scribe marks  $\frac{1}{4}$  S23 BT CS visible on open blaze.

A fir, 9 ins. diam., bears N.  $14^{\circ} E.$ , 9 lks. dist., with healed blaze.

N.  $0^{\circ} 02' E.$ , along the N. and S. center line of sec. 14, marking and blazing the true line.