

Dependent Resurvey of the East Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

15641

CHAINS

(Restoring the survey by Butler Ives and George W. Hyde,  
U. S. Deputy Surveyors, in 1854,  
the resurvey by William H. Byars,  
U. S. Deputy Surveyor, in 1882,  
and the resurvey by William M. Bushey,  
U. S. Deputy Surveyor, in 1894)

Beginning at the cor. of Tps. 31 and 32 S., Rs. 4 and 5 W  
perpetuated and recorded by Richard L. Templin, Jr.,  
Registered Engineer No. 3024, in 1958, monumented with  
an iron pipe, 1 in. diam., firmly set, protruding 6 ins.  
above ground, alongside of which is a basalt stone, 16 x  
10 x 10 ins., loosely set, 2 ins. in the ground, mkd.  
with 6 notches on each edge, from which the remains of  
the original bearing trees:

A fir stump, 39 ins. diam., bears N. 62° E., 33  
lks. dist., no marks visible.

and the remains of bearing trees mkd. by Bushey

A fir stump, 65 ins. diam., bears S. 76° E., 40  
lks. dist., with scribe mark S visible on  
opened blaze.

A fir, 35 ins. diam., bears S. 62° W., 60 lks.  
dist., with healed blaze. (Record, S. 66° W.,  
57 lks. dist.)

and a bearing tree mkd. by Templin

A cedar, 8 ins. diam., bears N. 25½° W., 25 lks.  
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 31 S  
R 5 W R 4 W  
S 36 | S 31  
S 1 | S 6  
T 32 S  
1973

from which new bearing trees

A fir, 14 ins. diam., bears N. 63° E., 47 lks.  
dist., mkd. T31S R4W S31 BT.

A fir, 12 ins. diam., bears S. 50° E., 53 lks.  
dist., mkd. T32S R4W S6 BT.

Deposit iron pipe and stone alongside iron post.

N. 0° 27' E., along the E. bdy. of sec. 36, marking and  
blazing the true line.

Descend 145 ft. over N. slope, through heavy timber and  
dense undergrowth.

3.40 Creek, 3 lks. wide, course N. 65° E.; asc. 130 ft. over  
SE. slope.

9.90 Spur, slopes N. 70° E.; desc. 150 ft. over NE. slope.