

15642

Dependent Resurvey of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS													
13.50	Creek, 1 lk. wide, course N. 65° E.; asc. 135 ft. over SE. slope.												
23.50	Spur, slopes N. 50° E.; desc. 265 ft. over broken NE. slope.												
34.10	Spur, slopes N. 30° E.; desc. 155 ft. over NE. slope.												
39.53	Point for the $\frac{1}{4}$ sec. cor. of sec. 36 only, determined by the method of irregular boundaries, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>$\frac{1}{4}$ S 36</td><td> </td></tr> <tr><td>T 31 S</td><td> </td></tr> <tr><td>R 5 W</td><td> </td></tr> <tr><td>1973</td><td></td></tr> </table> </div> from which A fir, 9 ins. diam., bears S. 10° W., 61 lks. dist., mkd. $\frac{1}{4}$ S36 BT. A fir, 7 ins. diam., bears S. 83° W., 50 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S36 BT. <hr style="width: 20%; margin: auto;"/> N. 0° 16' E., beginning new measurement. Descend 80 ft. over NE. slope.	$\frac{1}{4}$ S 36		T 31 S		R 5 W		1973					
$\frac{1}{4}$ S 36													
T 31 S													
R 5 W													
1973													
1.40	West Fork Russel Creek, 7 lks. wide, course E.; asc. 355 ft. over SE. slope.												
11.50	Spur, slopes S. 30° E.; desc. 110 ft. over NE. slope.												
22.30	Creek, 4 lks. wide, course S. 50° E.; asc. 325 ft. over broken SE. slope.												
33.50	Spur, slopes S. 70° E.; desc. 45 ft. along E. slope.												
37.00	Creek, 2 lks. wide, course S. 70° E.; asc. 110 ft. over SE. slope.												
39.58	The cor. of secs. 25 and 36 only, perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">COUNTY SURVEYORS OFFICE</td></tr> <tr><td>T 31 S R 4 W</td><td></td></tr> <tr><td>$\frac{S 25$</td><td> </td></tr> <tr><td>$\frac{S 36$</td><td> S 31</td></tr> <tr><td>R 5 W</td><td> </td></tr> <tr><td>1966</td><td></td></tr> </table> </div> from which the remains of the original bearing trees A fir snag, 29 ins. diam., bears N. 50° E., 45 lks. dist., with healed blaze. (Marks reported destroyed by Bushey, in 1894) A fir, 40 ins. diam., bears S. 32° E., 41 lks. dist., with healed blaze. (Marks reported destroyed by Bushey, in 1894)	COUNTY SURVEYORS OFFICE		T 31 S R 4 W		$\frac{S 25$		$\frac{S 36$	S 31	R 5 W		1966	
COUNTY SURVEYORS OFFICE													
T 31 S R 4 W													
$\frac{S 25$													
$\frac{S 36$	S 31												
R 5 W													
1966													