

15643

Dependent Resurvey of the East Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 30 ins. diam., bears S. 36° W., 35 lks. dist., with healed blaze.

A fir stump, 30 ins. diam., bears N. 54° W., 31 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by Powell

A cedar, 16 ins. diam., bears S. 51° E., 77 lks. dist., with scribe marks T31S 4W 3 visible on partially healed blaze.

A fir snag, 52 ins. diam., bears N. 60° E., 75 lks. dist., with healed blaze.

and new bearing trees

A fir, 4 ins. diam., bears S. 16° W., 10 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears N. 6° W., 30 lks. dist., mkd. T31S R5W S25 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, maple, chinquapin, and dogwood; undergrowth, vine maple, hazel, arrowwood, salal, and poison oak.

N. 0° 17' E., along the E. bdy. of sec. 25.

Ascend 110 ft. over SE. slope, through scattering timber and dense undergrowth.

3.62 From this point, the original closing cor. of secs. 30 and 31, T. 31 S., R. 4 W., bears West, 0.070 chs. dist., perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 4 W

S 25	S 30
R 5 W	S 31

1966

from which the remains of the original bearing trees

A fir snag, 40 ins. diam., bears N. 74° E., 73 lks. dist., with healed blaze.

A root hole, bears S. 81½° E., 61 lks. dist., with a down fir alongside, 30 ins. diam., no marks visible.

A fir stump, 40 ins. diam., bears S. 39½° W., 29 lks. dist., with scribe marks S 3 visible on opened blaze.

and bearing trees mkd. by Powell

A fir, 5 ins. diam., bears N. 80° E., 29 lks. dist., with healed blaze.