

15644

Dependent Resurvey of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir, 7 ins. diam., bears N. 20° E., 26 lks. dist., with scribe marks BT visible on partially healed blaze.

Ascend 165 ft. over SE. slope.

- 8.65 Dirt road, 15 lks. wide, in curve, bears N. 65° E. and S. 55° W.
- 9.70 Ridge, bears N. 85° E. and S. 75° W.; desc. 625 ft. over NW. slope.
- 24.10 Ravine, drains N. 30° E.; desc. 50 ft. along E. slope.
- 27.60 Bottom of descent, slopes E.; asc. 25 ft. over SE. slope.
- 39.11 Point for the $\frac{1}{4}$ sec. cor. of sec. 25 only, determined by the method of irregular boundaries, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 25	
T 31 S	
R 5 W	
1973	

from which

A fir, 25 ins. diam., bears S. 36° W., 63 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

A fir, 20 ins. diam., bears N. 38° W., 31 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

N. 0° 30' E., beginning new measurement.

Ascend 25 ft. over SE. slope.

- 1.10 Top of ascent, slopes E.; desc. 480 ft. over N. slope.
- 12.00 Ravine, drains N. 40° E.; desc. 175 ft. over broken NE. slope.
- 17.10 Ravine, drains N. 60° E.; desc. 105 ft. over broken NE. slope.
- 21.90 Ravine, drains N. 70° E.; asc. 35 ft. along E. slope.
- 24.20 Spur, slopes E.; desc. 100 ft. over NE. slope.
- 28.90 Ravine, drains N. 55° E.; asc. 80 ft. over SE. slope.
- 33.80 Spur, slopes E.; desc. 60 ft. over NE. slope.
- 36.00 Ravine, drains S. 80° E.; asc. 45 ft. over SE. slope.
- 38.66 The cor. of secs. 24 and 25 only, perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S		R 4 W
S 24		S 30
S 25		
R 5 W		
1966		