

15646

Dependent Resurvey of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS
39.82

Point for the $\frac{1}{4}$ sec. cor. of sec. 24 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

FD OK 2/96
BY LANE M 127-73

$\frac{1}{4}$ S 24
T 31 S
R 5 W
1973

from which

A hemlock, 10 ins. diam., bears S. $68\frac{1}{2}^\circ$ W., $43\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A fir, 8 ins. diam., bears N. $6\frac{1}{2}^\circ$ W., 47 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Descend 25 ft. over NW. slope.

44.10 Creek, 3 lks. wide, course N. 25° E.; asc. 300 ft. over SE. slope.

59.73 Point for the N $1/16$ sec. cor. of sec. 24 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

N $1/16$
S 24
1973

from which

A fir, 6 ins. diam., bears S. $69\frac{1}{2}^\circ$ W., 98 lks. dist., mkd. N $1/16$ S24 BT.

A madrone, 12 ins. diam., bears N. 39° W., $45\frac{1}{2}$ lks. dist., mkd. N $1/16$ S24 BT.

Ascend 340 ft. over SE. slope.

75.70 Gravelled road, 15 lks. wide, bears N. 40° E. and S. 40° W.

76.90 Ridge, bears NE. and SW.; desc. 120 ft. over NW. slope.

79.64 The cor. of secs. 13 and 24 only, perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R T 31 S | R
S S 13 | S 19 4
W S 24 | W
1966

from which the remains of the original bearing trees

A fir, 44 ins. diam., bears N. 21° E., 23 lks. dist., with healed blaze.

A fir snag, 29 ins. diam., bears S. 58° W., 20 lks. dist., with scribe marks BT visible on opened blaze.