

Dependent Resurvey of the East Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Powell

A cedar, 7 ins. diam., bears N. 70° E., 31 lks. dist., with healed double blaze.

A fir, 5 ins. diam., bears N. 40° W., 29 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. 32° W., 52 lks. dist., mkd. T31S R5W S24 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, chinquapin, maple, and madrone; undergrowth, vine maple, hazel, salal, fern, and poison oak.

N. 0° 21' E., along the E. bdy. of sec. 13.

Descend 160 ft. over broken NW. slope, through heavy timber and dense undergrowth.

5.85 From this point, the original closing cor. of secs. 18 and 19, T. 31 S., R. 4 W., bears West, 0.065 chs. dist., perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, protruding 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R	T 31 S	R
5 S 13	S 18	4
W	S 19	W
1966		

from which the remains of the original bearing trees

A cedar, 35 ins. diam., bears S. 54° E., 62 lks. dist., with healed blaze.

A root hole, bears S. 14½° W., 33 lks. dist., with a down fir alongside, 30 ins. diam., no marks visible.

and a bearing tree mkd. by Powell

A fir, 13 ins. diam., bears N. 62½° E., 36 lks. dist., with healed blaze.

Descend 95 ft. over NW. slope.

8.30 Ravine, drains N. 85° W.; asc. 90 ft. over SW. slope.

12.00 Spur, slopes W.; desc. 15 ft. over NW. slope.

14.30 Ravine, drains S. 70° W.; asc. 85 ft. over SW. slope.

18.60 Spur, slopes W.; desc. 460 ft. over NW. slope.

32.00 Creek, 4 lks. wide, course S. 85° W.; asc. 140 ft. over SW. slope.

40.02 Point for the ¼ sec. cor. of sec. 13 only, determined by the method of irregular boundaries, there is no remaining evidence of the original corner.