

15648

Dependent Resurvey of the East Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 13 |  
T 31 S |  
R 5 W |  
1973

from which

A fir, 8 ins. diam., bears S.  $20^\circ$  W.,  $46\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

A fir, 6 ins. diam., bears N.  $81\frac{1}{2}^\circ$  W.,  $54\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

N.  $0^\circ 08'$  E., beginning new measurement.

Ascend 5 ft. over SW. slope.

0.80 Spur, slopes W.; desc. 10 ft. over NW. slope.

2.10 Creek, 2 lks. wide, course S.  $5^\circ$  W.; asc. 100 ft. over SE. slope.

5.97 From this point, the  $\frac{1}{4}$  sec. cor. of sec. 18 only, T. 31 S., R. 4 W., established by the County Surveyor's Office, in 1966, bears West, 0.080 chs. dist., monumented with an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S | R 4 W  
R  $\frac{1}{4}$  | S 18  
5  
W 1966

from which bearing trees mkd. by the County

A fir, 17 ins. diam., bears N.  $46^\circ$  E.,  $79\frac{1}{2}$  lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S.  $24^\circ$  E., 39 lks. dist., with healed blaze.

Ascend 605 ft. over broken SE. slope.

28.30 Ridge, bears N.  $55^\circ$  E. and S.  $55^\circ$  W.; desc. 190 ft. over NW. slope.

35.00 Top of rock bluff, 30 ft. high, bears E. and W.; desc. 220 ft. over NW. slope.

39.66 Point for the cor. of secs. 12 and 13 only; determined by the method of irregular boundaries, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 31 S | T 31 S  
S 12 | R 4 W  
S 13 |  
R 5 W | S 18  
1973