

Dependent Resurvey of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 10 ins. diam., bears S. 79° W., 39 lks.
dist., mkd. T31S R5W S13 BT.

A fir, 12 ins. diam., bears N. 53½° W., 66 lks.
dist., mkd. T31S R5W S12 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, live oak, maple, and
chinquapin; undergrowth, vine maple, hazel, arrowwood,
salal, fern, and poison oak.

N. 0° 18' W., along the E. bdy. of sec. 12.

Descend 60 ft. over NW. slope, through heavy timber and
dense undergrowth.

1.20 Ravine, drains N. 70° W.; asc. 100 ft. over SW. slope.

6.45 From this point, the original closing cor. of secs. 7 and
18, T. 31 S., R. 4 W., bears East, 0.020 chs. dist.,
perpetuated by John M. Powell, Deputy County Surveyor,
in 1966, monumented with an iron post, 1½ ins. diam.,
firmly set, protruding 10 ins. above ground, with brass
cap mkd.

COUNTY SURVEYORS OFFICE

R	T 31 S	R
5 S 12	S 7	4
W	S 18	W

1966

from which the remains of the original bearing trees

A fir, 25 ins. diam., bears N. 87½° W., 33 lks.
dist., with illegible scribe marks visible on
opened blaze.

and bearing trees mkd. by Powell

A madrone, 7 ins. diam., bears N. 41° E., 7½ lks.
dist., with scribe marks T31S R4W S7 CS BT
visible on partially healed blaze.

A madrone, 8 ins. diam., bears S. 54° E., 34 lks.
dist., with scribe marks T31S R4W S18 CS BT
visible on partially healed blaze.

Ascend 30 ft. over SW. slope.

9.00 Spur, slopes N. 50° W.; desc. 470 ft. over NE. slope.

19.325 Point for the S 1/16 sec. cor. of sec. 12 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S 1/16	
S 12	
1973	

from which

*FOR COR. REV.
SEE CS 63/104
11/15/90*