

15650

Dependent Resurvey of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears S. 58° W., 38 lks.
dist., mkd. S 1/16 S12 BT.

A fir, 36 ins. diam., bears N. 59° W., 117½ lks.
dist., mkd. S 1/16 S12 BT.

Descend 20 ft. over NE. slope.

20.10 Ravine, drains N. 40° W.; asc. 45 ft. over SW. slope.

22.60 Spur, slopes N. 65° W.; desc. 35 ft. over NW. slope.

23.90 Ravine, drains N. 80° W.; asc. 230 ft. over SW. slope.

30.00 Top of ascent, slopes W.; desc. 70 ft. over NW. slope.

33.50 Ravine, drains S. 70° W.; asc. 230 ft. over SW. slope.

38.65 Point for the ¼ sec. cor. of sec. 12 only, determined by
the method of irregular boundaries, there is no remaining
evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

¼ S 12
T 31 S
R 5 W
1973

from which

A fir, 7 ins. diam., bears S. 34½° W., 65 lks.
dist., mkd. ¼ S12 BT.

A fir, 6 ins. diam., bears N. 88° W., 61 lks.
dist., mkd. ¼ S12 BT.

N. 0° 24' E., beginning new measurement.

Ascend 45 ft. over SW. slope.

1.30 Spur, slopes N. 85° W.; desc. 680 ft. over NW. slope.

18.00 Bear Gulch, drains S. 60° W.; asc. 320 ft. over broken
S. slope.

37.70 Spur, slopes S. 40° W.; desc. 10 ft. over NW. slope.

38.56 The cor. of secs. 1 and 12 only, perpetuated by John M.
Powell, Deputy County Surveyor, in 1966, monumented with
an iron post, 1½ ins. diam., firmly set, protruding 12
ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 4 W

S 1
S 12 | S 7
R 5 W
1966

from which a bearing tree mkd. by Bushey

A fir, 39 ins. diam., bears S. 13° W., 109½ lks.
dist., with illegible scribe marks visible on
opened blaze.