

Dependent Resurvey of a Portion of the North Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Nathaniel Ford,  
U. S. Deputy Surveyor, in 1854,  
the resurvey by William H. Byars,  
U. S. Deputy Surveyor, in 1882,  
and the resurvey by John M. Jelley,  
Lynn M. Roseberry, and Floyd A. Brooks,  
Cadastral Surveyors, in 1966-68)

From the cor. of secs. 1 and 2 only, perpetuated and re-  
corded by V. S. King, RLS No. 442, in 1959, monumented  
with an iron post, 2½ ins. diam., firmly set, protruding  
5 ins. above ground, with brass cap mkd.

T 30 S R 5 W  
S 36  
S 2 | S 1  
T 31 S R 5 W  
1967

from which the remains of the original bearing trees

A fir snag, 19 ins. diam., bears N. 40° E., 26  
lks. dist., with healed blaze. Rescribed RS  
442 S36 T30S R5W BT on bark blaze, by King.

A fir, 45 ins. diam., bears S. 20° W., 52 lks.  
dist., with illegible scribe marks visible on  
bark blaze. Rescribed S2 T31S R5W BT on bark  
blaze, by King.

A dogwood root crown, size indeterminate, bears  
N. 28° W., 15 lks. dist.

and bearing trees mkd. by King

A fir, 40 ins. diam., bears S. 51° E., 55 lks.  
dist., with scribe marks RS 442 S1 T31S R5W BT  
visible on bark blaze.

A dogwood, 7 ins. diam., bears N. 15° W., 11 lks.  
dist., with healed blaze.

N. 89° 43' W., along the N. bdy. of sec. 2, marking and  
blazing the true line.

Ascend 50 ft. over NE. slope, across partially logged  
area, through scattering timber and dense undergrowth.

1.20 The cor. of secs. 35 and 36 only, T. 30 S., R. 5 W.,  
monumented with an iron post, 2½ ins. diam., firmly  
set, protruding 5 ins. above ground, with brass cap mkd.

T 30 S R 5 W  
S 35 | S 36  
S 2  
T 31 S R 5 W  
1967

from which bearing trees mkd. by Jelley, Roseberry, and  
Brooks

A fir, 42 ins. diam., bears N. 7½° E., 100 lks.  
dist., with healed blaze.

A fir, 11 ins. diam., bears N. 39½° W., 149 lks.  
dist., with healed blaze.