

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS 15.65	Ridge, bears N. 25° E. and S. 25° W.; desc. 395 ft. over W. slope.
24.25	Creek, 1 lk. wide, course N. 65° W.; desc. 190 ft. over NW. slope.
34.40	Ravine, drains N. 15° W.; asc. 130 ft. over NE. slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4} \begin{array}{l} S 25 \\ S 36 \end{array}$ T 31 S R 5 W 1973 from which A fir, 15 ins. diam., bears N. $30\frac{3}{4}$ ° E., $6\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S25 BT. A fir, 11 ins. diam., bears S. $87\frac{1}{2}$ ° W., $22\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S36 BT. Corner is located on spur, slopes N. Descend 45 ft. over NW. slope.
42.00	Bottom of descent, slopes N.; asc. 50 ft. over NE. slope.
47.87	Spur, slopes N. 40° W.; desc. 835 ft. over W. slope.
72.90	Creek, 2 lks. wide, course N. 50° W.; asc. 40 ft. over broken N. slope.
79.96	The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., protruding 6 ins. above ground, with brass cap mkd. $\begin{array}{l} T 31 S R 5 W \\ S 26 S 25 \\ S 35 S 36 \\ 1955 \end{array}$ from which bearing trees mkd. by Thielsen A sawed fir stump, 26 ins. diam., bears N. 47° E., 6 lks. dist., with illegible scribe marks visible on open blaze. A fir, 39 ins. diam., bears S. 51° E., 55 lks. dist., with healed blaze. A sawed fir stump, 32 ins. diam., bears S. $62\frac{1}{2}$ ° W., 111 lks. dist., with healed blaze. A sawed fir stump, 24 ins. diam., bears N. $43\frac{1}{2}$ ° W., 27 lks. dist., with healed blaze. and bearing trees mkd. by the County