

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS  
79.48

Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance, falls on east edge of abandoned highway, 40 lks. wide, bears N. 15° E. and S.; there is no remaining evidence of the original corner.

Set a brass tablet, 3½ ins. diam., 3½ ins. stem, in drill hole, in concrete highway surface, with top mkd.

T 31 S R 5 W  
S 23 | S 24  
S 26 | S 25  
1973

from which

A fir, 17 ins. diam., bears N. 15° E., 95 lks. dist., mkd. T31S R5W S24 BT.

A fir, 10 ins. diam., bears S. 55° E., 102 lks. dist., mkd. T31S R5W S25 BT.

A fir, 13 ins. diam., bears S. 22° W., 94½ lks. dist., mkd. T31S R5W S26 BT.

A fir, 19 ins. diam., bears N. 60° W., 123½ lks. dist., mkd. T31S R5W S23 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, madrone, chinquapin, and maple, undergrowth, vine maple, hazel, salal, fern, and poison oak.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp.

S. 88° 54' W., bet. secs. 24 and 25.

Ascend 270 ft. over E. slope, through scattered timber and heavy undergrowth.

9.45 Ridge, bears N. 20° E. and S. 15° W.; desc. 350 ft. over W. slope.

19.5 Gravelled road, 30 lks. wide, bears S. 15° E. and N. 10° W.; enter logged area, edge bears W. and N.

19.62 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 S 24  
S 25  
1973

from which

A fir, 8 ins. diam., bears N. 49° E., 107 lks. dist., mkd. E 1/16 S24 BT.

A grand fir, 12 ins. diam., bears S. 30° W., 37 lks. dist., mkd. E 1/16 S25 BT.

Descend 150 ft. over broken W. slope.