

15660

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
27.40	Creek, 1 lk. wide, course N. 40° E.; asc. 320 ft. over E. slope.
39.24	The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.
	<p>FD. OK 2/96 BY LANG M/27-13</p> <p>COUNTY SURVEYORS OFFICE T 31 S R 5 W $\frac{1}{4}$ S 24 S 25 1966</p> <p>from which the remains of the original bearing trees</p> <p>A sawed fir stump, 15 ins. diam., bears N. 23° E., 74 lks. dist., with scribe marks BT visible on bark.</p> <p>and bearing trees mkd. by Powell</p> <p>A fir, 24 ins. diam., bears N. 43° E., 31 lks. dist., with healed blaze.</p> <p>A cedar, 8 ins. diam., bears S. 38° W., 49 lks. dist., with scribe marks $\frac{1}{4}$ S25 BT visible on open blaze.</p> <p>N. 88° 55' W., beginning new measurement.</p> <p>Ascend 55 ft. over E. slope, through heavy timber and dense undergrowth.</p>
2.30	Ridge, bears N. 15° E. and S. 5° E.; desc. 590 ft. over broken SW. slope.
28.65	Creek, 4 lks. wide, course N. 60° W.; asc. 35 ft. over NE. slope.
30.95	Spur, slopes N. 20° W.; desc. 75 ft. over W. slope.
34.45	Same creek, 4 lks. wide, course S. 40° W.; asc. 100 ft. over SE. slope.
40.69	The cor. of secs. 23, 24, 25, and 26.
	<p>Land, mountainous. Soil, rocky clay with rock outcroppings. Timber, fir, cedar, hemlock, madrone, alder, maple, pine, oak, and dogwood; undergrowth, poison oak, salal, fern, hazel, arrowwood, and vine maple.</p> <p>N. 1° 22' E., bet. secs. 23 and 24.</p> <p>Descend 60 ft. over NW. slope, across cleared area of Interstate Highway No. 5, right-of-way.</p>
3.45	Canyon Creek, 3 lks. wide, course N. 10° E.; asc. 90 ft. over broken E. slope.
6.80	Center of northbound lane, Interstate Highway No. 5, 60 lks. wide, bears S. 30° W. and N. 20° E.