

15662

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A live oak, 22 ins. diam., bears N. 50° E., 49 lks. dist., no marks visible. (Record, 52 lks.)

A yew, 15 ins. diam., bears S. 50° E., 17 lks. dist., with scribe marks X BT visible on bark.

A fir, 12 ins. diam., bears S. 27° W., 8 lks. dist., with scribe mark T visible on opened blaze.

A fir stump, 24 ins. diam., bears N. 48° W., 24 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

*FO. OK 2/96
BI LANG M 127-73*

T 31 S R 5 W
S 14 | S 13
S 23 | S 24
1973

from which new bearing trees

A fir, 10 ins. diam., bears N. 20° E., 23 lks. dist., mkd. T31S R5W S13 BT.

A fir, 8 ins. diam., bears S. 51½° E., 44½ lks. dist., mkd. T31S R5W S24 BT.

A fir, 14 ins. diam., bears S. 64½° W., 8 lks. dist., mkd. T31S R5W S23 BT.

A fir, 9 ins. diam., bears N. 51° W., 33½ lks. dist., mkd. T31S R5W S14 BT.

Deposit corner stone alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, madrone, yew, chinquapin, maple, and oak; undergrowth, hazel, vine maple, fern, salal, poison oak, and rhododendron.

From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp.

S. 89° 56' W., bet. secs. 13 and 24.

Descend 50 ft. over broken N. slope, through heavy timber and dense undergrowth.

10.40 Ravine, drains N.; asc. 210 ft. over NE. slope.

23.05 Spur ridge, slopes N. 70° W.; desc. 235 ft. over SW. slope.

29.30 Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.

31.90 Ravine, drains S.; asc. 120 ft. over SE. slope.

32.70 Dirt road, 15 lks. wide, bears N. 55° E. and S. 25° W.

37.40 Spur, slopes S. 15° W.; desc. 105 ft. over SW. slope.

38.83 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

n the
ruly
the