

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

FD OK 2196 BY LANG
M 127-73

S 13
S 24
T 31 S R 5 W
1973

from which

A madrone, 8 ins. diam., bears N. 3½° W., 24 lks. dist., mkd. ¼ S13 BT.

A madrone, 9 ins. diam., bears S. 8½° E., 27½ lks. dist., mkd. ¼ S24 BT.

Descend 525 ft. over SW. slope.

42.33 Dirt road, 15 lks. wide, bears N. 45° W. and S. 40° E.

46.75 Power transmission lines, bears N. 20° W. and S. 20° E.

58.245 Point for the W 1/16 sec. cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 13
S 24
1973

from which

A fir, 10 ins. diam., bears N. 85½° E., 25½ lks. dist., mkd. W 1/16 S13 BT.

A fir, 12 ins. diam., bears S. 31½° W., 14 lks. dist., mkd. W 1/16 S24 BT.

Descend 295 ft. over SW. slope.

70.70 Wire fence, bears N. and S.

73.00 Canyon Creek, 10 lks. wide, course N.; asc. 25 ft. across cleared area of Interstate Highway No. 5 right-of-way.

73.80 Center of northbound lanes, Interstate Highway No. 5, 60 lks. wide, bears N. and S.

75.10 Center of southbound lanes of Interstate Highway No. 5, 60 lks. wide, bears same.

77.66 The cor. of secs. 13, 14, 23, and 24.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, pine, hemlock, cedar, madrone, oak, dogwood, and maple; undergrowth, hazel, poison oak, fern, vine maple, and arrowwood.

N. 1° 48' W., bet. secs. 13 and 14.

Descend 30 ft. over NE. slope, through heavy timber and dense undergrowth.

2.00 Creek, 1 lk. wide, course E.; asc. 125 ft. over SE. slope.