

15664

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS 7.75	Spur, slopes N. 55° E.; desc. 205 ft. over NE. slope.
15.00	Creek, 2 lks. wide, course N. 70° E.; asc. 355 ft. over SE. slope.
19.835	Point for the S 1/16 sec. cor. of secs. 13 and 14.  Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  S 1/16 S 14   S 13 1973  from which  A live oak, 8 ins. diam., bears N. 84° E., 26½ lks. dist., mkd. S 1/16 S13 BT.  A fir, 9 ins. diam., bears S. 35° W., 77 lks. dist., mkd. S 1/16 S14 BT.  Ascend 65 ft. over SE. slope.
23.50	Spur, slopes N. 65° E.; desc. 50 ft. over NE. slope.
24.90	Creek, 1 lk. wide, course E.; asc. 210 ft. over SE. slope.
39.67	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  FD OK BY LANE 2/96 M 127-73  ¼ S 14   S 13 T 31 S R 5 W 1973  from which  A fir, 11 ins. diam., bears N. 70° E., 38 lks. dist., mkd. ¼ S13 BT.  A fir, 10 ins. diam., bears N. 67° W., 21 lks. dist., mkd. ¼ S14 BT.  Ascend 100 ft. over SE. slope.
55.40	Spur, slopes N. 30° E.; desc. 125 ft. over NE. slope.
59.50	Ravine, drains N. 60° E.; asc. 35 ft. over SE. slope.
61.00	Spur, slopes N. 40° E.; desc. 310 ft. over NE. slope.
72.00	Ravine, drains N. 40° E.; asc. 195 ft. over SE. slope.
79.34	Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.