

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 31 S R 5 W
S 11 | S 12
S 14 | S 13
1973

from which

A fir, 15 ins. diam., bears N. 66½° E., 3 lks. dist., mkd. T31S R5W S12 BT.

A fir, 8 ins. diam., bears S. 13½° E., 22 lks. dist., mkd. T31S R5W S13 BT.

A fir, 17 ins. diam., bears S. 48° W., 23 lks. dist., mkd. T31S R5W S14 BT.

A fir, 7 ins. diam., bears N. 22° W., 35 lks. dist., mkd. T31S R5W S11 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, live oak, madrone, maple, and chinquapin; undergrowth, arrowwood, poison oak, vine maple, hazel, and salal.

From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp.

S. 89° 42' W., bet. secs. 12 and 13.

Descend 340 ft. over NW. slope, through heavy timber and dense undergrowth.

12.20 Ravine, drains N. 20° W.; asc. 160 ft. over NE. slope.

17.65 Spur, slopes N. 20° E.; desc. 25 ft. over NW. slope.

20.105 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 12
S 13
1973

*FOR COR. REV.
SEE CS 63/104
11/15/90*

from which

A fir, 8 ins. diam., bears N. 34° W., 53 lks. dist., mkd. E 1/16 S12 BT.

A fir, 8 ins. diam., bears S. 23° W., 7 lks. dist., mkd. E 1/16 S13 BT.

Descend 10 ft. over NW. slope.

20.60 Bottom of descent, slopes N.; asc. 50 ft. over NE. slope.

25.70 Spur, slopes N.; desc. 430 ft. over NW. slope.

32.30 Power transmission lines, bears N. 10° E. and S. 10° W.

40.21 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.