

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS  
17.75

Ridge, bears N. 20° E. and S. 40° W.; desc. 5 ft. over NW. slope.

19.845

Point for the S 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 11|S 12  
1973

from which

A fir, 8 ins. diam., bears S. 59½° E., 42 lks. dist., mkd. S 1/16 S12 BT.

A fir, 10 ins. diam., bears S. 8½° W., 87 lks. dist., mkd. S 1/16 S11 BT.

Descend 200 ft. over broken NW. slope.

39.69

Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼  
S 11|S 12  
T 31 S R 5 W  
1973

from which

A fir, 17 ins. diam., bears S. 22½° E., 57½ lks. dist., mkd. ¼ S12 BT.

A fir, 12 ins. diam., bears N. 29½° W., 44 lks. dist., mkd. ¼ S11 BT.

Descend 200 ft. over broken NW. slope.

59.535

Point for the N 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16  
S 11|S 12  
1973

from which

A fir, 15 ins. diam., bears S. 86½° E., 95½ lks. dist., mkd. N 1/16 S12 BT.

A fir, 8 ins. diam., bears S. 87½° W., 79 lks. dist., mkd. N 1/16 S11 BT.

Descend 405 ft. over broken NW. slope.

77.15

Canyon Creek, 5 lks. wide, course W., enter cleared area of highway right-of-way, edge bears N. 75° W. and S. 75° E.; asc. 5 ft. over SW. slope.