

15668

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
78.75	Center of southbound lanes, Interstate Highway No. 5, 60 lks. wide, bears N. 75° W. and S. 75° E.
79.38	<p>The cor. of secs. 1, 2, 11, and 12, located in center of northbound lanes, Interstate Highway No. 5, 60 lks. wide, bears N. 75° W. and S. 75° E. The corner is determined from a witness corner established by James W. Byron and John M. Powell, Deputy County Surveyors, in 1969, when original corner evidence was still in existence.</p> <p>An iron post, 1½ ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, 1½ ft. high, bears South, 5.03 chs. dist., with brass cap mkd. T31S R5W WC 332' N to S1 S2 S11 S12 1969, from which bearing trees mkd. by Byron and Powell:</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 85° E., 46 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 48° W., 25 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Drive a galvanized nail, 2 ins. long, ¼ in. diam., flush with asphaltic surface of highway.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. 40° E., 299 lks. dist., mkd. T31S R5W S1 BT.</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears N. 19° W., 371 lks. dist., mkd. T31S R5W S2 BT.</p> <p style="padding-left: 40px;">No other suitable trees available within limits.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, madrone, live oak, maple, and chinquapin; undergrowth, vine maple, hazel, salal, arrowwood, fern, and poison oak.</p>
	From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp.
	N. 88° 43' W., bet. secs. 1 and 12.
	Descend 180 ft. over W. slope, through heavy timber and dense undergrowth.
3.75	Ravine, drains S. 60° W.; desc. 65 ft. over SW. slope.
7.55	Creek, 1 lk. wide, course S. 5° W.; asc. 90 ft. over SE. slope.
10.70	Top of ascent, slopes S.; desc. 35 ft. over SW. slope.
14.90	Bottom of descent, slopes S.; asc. 130 ft. over SE. slope.
19.27	<p>Point for the E 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

area