

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

E 1/16  $\frac{S 1}{S 12}$   
1973

from which

A cedar, 9 ins. diam., bears N. 86° E., 33½ lks.  
dist., mkd. E 1/16 S1 BT.

A fir, 11 ins. diam., bears S. 1° E., 71½ lks.  
dist., mkd. E 1/16 S12 BT.

Ascend 45 ft. over SE. slope.

21.60 Spur, slopes S.; desc. 325 ft. over broken SW. slope.

25.20 Power transmission lines, bears N. and S.

38.54 Point for the ¼ sec. cor. of secs. 1 and 12, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

¼  $\frac{S 1}{S 12}$   
T 31 S R 5 W  
1973

from which

A fir, 10 ins. diam., bears N. 12° W., 62 lks.  
dist., mkd. ¼ S1 BT.

A fir, 20 ins. diam., bears S. 61° W., 48 lks.  
dist., mkd. ¼ S12 BT.

Descend 265 ft. over SW. slope.

51.25 Creek, 2 lks. wide, course S. 10° E.; asc. 80 ft. over  
SE. slope.

51.80 Gravelled road, 20 lks. wide, bears N. 30° E. and  
S. 30° W., curving S.

55.00 Spur, slopes S. 10° E., enter cleared area of highway  
right-of-way, edge bears N. 10° W. and S. 10° E.; desc.  
135 ft. over SW. slope.

77.08 The cor. of secs. 1, 2, 11, and 12.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, live oak, madrone, maple,  
and chinquapin; undergrowth, hazel, arrowwood, salal,  
vine maple, poison oak, and fern.

N. 0° 33' E., bet. secs. 1 and 2.

Ascend 500 ft. over SW. slope, across cleared area of  
highway right-of-way.

3.50 Enter heavy timber and dense undergrowth, edge bears  
N. 70° W. and S. 70° E.