

15672

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS  
81.46

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

T 31 S R 5 W  
S 22 | S 23  
S 27 | S 26  
1955

from which the remains of the original bearing trees

A fir, 35 ins. diam., bears S. 45° E., 30 lks. dist., with scribe marks BT visible on open blaze.

and bearing trees mkd. by Thielsen, in 1955

A fir, 32 ins. diam., bears S. 14° E., 35 lks. dist., with healed blaze.

A fir stump, 21 ins. diam., bears S. 31° W., 43 lks. dist., with illegible scribe marks visible on open blaze.

A fir, 32 ins. diam., bears N. 68° W., 35 lks. dist., with healed blaze.

and bearing trees mkd. by the County

A fir, 19 ins. diam., bears S. 25° W., 46 lks. dist., with healed blaze.

A madrone, 18 ins. diam., bears N. 8° W., 33 lks. dist., with scribe marks T31S R5W S22 BT visible on open blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, maple, chinquapin, and live oak; undergrowth, hazel, vine maple, fern, salal, rhododendron, arrowwood, and poison oak.

N. 0° 54' E., bet. secs. 22 and 23.

Ascend 365 ft. over SE. slope, through light timber and undergrowth.

10.70 Gravelled road, 20 lks. wide, bears N. 65° E. and S. 65° W.

15.20 Ridge, bears N. 30° E. and S. 30° W.; desc. 225 ft. over broken NW. slope.

16.20 Dirt road, 10 lks. wide, bears N. 55° E. and S. 15° W.

37.05 Gravelled road, 20 lks. wide, bears N. 40° E. and S. 20° W.

40.02 Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.