

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 31 S R 5 W

$$\begin{array}{c} \frac{1}{2} \\ \hline S 22 | S 23 \\ 1973 \end{array}$$

from which

A sugar pine, 14 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ E.,
83 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S23 BT.

A fir, 12 ins. diam., bears N. 19° W., 48 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{2}$ S22 BT.

Corner is located on spur, slopes W.

Descend 140 ft. over NW. slope.

- 48.05 Bottom of descent, slopes W.; asc. 50 ft. over SW.
slope.
- 52.55 Spur, slopes N. 45° W.; desc. 455 ft. over N. slope.
- 62.15 Dry creek, 4 lks. wide, course N. 70° W.; asc. 140 ft.
over SW. slope.
- 68.95 Spur, slopes N. 45° W.; desc. 205 ft. over N. slope.
- 80.04 The cor. of secs. 14, 15, 22, and 23, perpetuated and re-
corded by Victor S. King, RLS No. 442, in 1909, further
perpetuated and recorded by John M. Powell, Deputy
County Surveyor, in 1966, monumented with an iron pipe,
1 $\frac{1}{2}$ ins. diam., firmly set, protruding 8 ins. above
ground, from which the remains of the original bearing
trees:
- A madrone, 9 ins. diam., bears N. 5° E., 20 lks.
dist., no marks visible on decayed blaze.
- A fir, 35 ins. diam., bears S. 50° W., 35 lks.
dist., with healed blaze.
- A live oak, 14 ins. diam., bears N. 25° W., 50
lks. dist., with healed blaze.
- and bearing trees mkd. by King
- A sugar pine snag, 10 ins. diam., bears N. 10° E.,
49 lks. dist., with scribe marks T31S R5 S14 BT
visible on open blaze.
- A fir, 19 ins. diam., bears S. 49° E., 43 lks.
dist., with healed blaze.
- and a bearing tree mkd. by Powell
- A madrone, 9 ins. diam., bears N. 7° E., 23 lks.
dist., with scribe marks T31S R5W S14 BT visible
on open blaze.
- At the corner point
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

$$\begin{array}{c} T 31 S R 5 W \\ \hline S 15 | S 14 \\ \hline S 22 | S 23 \\ 1972 \end{array}$$

FD. OK
B. SHANER
6/92
M112-49