

15674

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Deposit iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, madrone, live oak,  
chinquapin, and maple; undergrowth, hazel, arrowwood,  
vine maple, salal, fern, and poison oak.

From the cor. of secs. 13, 14, 23, and 24.

N. 89° 59' W.; bet. secs. 14 and 23.

Ascend 545 ft. over E. slope, through heavy timber and  
dense undergrowth.

19.05 Ridge, bears N. 40° E. and S. 30° W.; desc. 365 ft. over  
NW. slope.

30.85 Creek, 3 lks. wide, course N. 25° E.; asc. 325 ft. over  
NE. slope.

41.02 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 14}{S\ 23}$   
T 31 S R 5 W  
1973

from which

A fir, 8 ins. diam., bears N. 30° E., 43 lks.  
dist., mkd.  $\frac{1}{4}$  S14 BT.

A fir, 7 ins. diam., bears S. 12° W., 39 lks.  
dist., mkd.  $\frac{1}{4}$  S23 BT.

Ascend 415 ft. over broken NE. slope.

55.30 Gravelled road, 10 lks. wide, bears N. 5° W. and  
S. 5° E.

56.00 Ridge, bears N. 5° W. and S. 5° E.; desc. 215 ft. over  
W. slope.

61.53 Point for the W 1/16 sec. cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

W 1/16  $\frac{S\ 14}{S\ 23}$   
1973

FD BC+ BT  
2 NEW 5/8 IRs  
R QUIMBY  
2/2020  
CS65/104-66

from which

A fir, 11 ins. diam., bears N. 55° E., 75 lks.  
dist., mkd. W 1/16 S14 BT.

A pine, 13 ins. diam., bears S. 45 $\frac{1}{2}$ ° W., 10 lks.  
dist., mkd. W 1/16 S23 BT.

Descend 290 ft. over W. slope.