

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS			CH 19.										
71.50		Bottom of descent, slopes NW.; asc. 20 ft. over NE. slope.											
76.70		Spur, slopes N. 40° W.; desc. 120 ft. over SW. slope.											
82.04		The cor. of secs. 14, 15, 22, and 23.											
		Land, mountainous. Soil, rocky clay. Timber, fir, cedar, pine, hemlock, madrone, live oak, maple, and chinquapin; undergrowth, hazel, salal, arrow-wood, vine maple, poison oak, and fern.											
		N. 0° 28' E., bet. secs. 14 and 15.											
		Ascend 35 ft. over SW. slope, through heavy timber and light undergrowth.											
2.30		Spur, slopes N. 65° W.; desc. 165 ft. over N. slope.											
6.35		Gravelled road, 20 lks. wide, bears N. 65° W. and S. 60° E.											
6.50		Dry creek, 4 lks. wide, course N. 65° W.; asc. 285 ft. over SW. slope.											
11.65		Gravelled road, 20 lks. wide, bears N. 60° E. and S. 80° W.											
19.80		The S 1/16 sec. cor. of secs. 14 and 15, established by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, protruding 12 ins. above ground.											
		At the corner point											
		Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.											
		<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 1/16</td> <td style="text-align: right;">FD BC+1 BT</td> </tr> <tr> <td style="text-align: center;">S 15 S 14</td> <td style="text-align: right;">5 NEW 5/8 IRS</td> </tr> <tr> <td style="text-align: center;">1973</td> <td style="text-align: right;">R QUIMBY</td> </tr> <tr> <td></td> <td style="text-align: right;">2/2020</td> </tr> <tr> <td></td> <td style="text-align: right;">CS65/104-53</td> </tr> </table>	S 1/16	FD BC+1 BT	S 15 S 14	5 NEW 5/8 IRS	1973	R QUIMBY		2/2020		CS65/104-53	
S 1/16	FD BC+1 BT												
S 15 S 14	5 NEW 5/8 IRS												
1973	R QUIMBY												
	2/2020												
	CS65/104-53												
		from which											
		A fir, 7 ins. diam., bears S. 51° E., 62 lks. dist., mkd. S 1/16 S14 BT.											
		A live oak, 6 ins. diam., bears S. 41½° W., 40 lks. dist., mkd. S 1/16 S15 BT.											
		Deposit iron pipe alongside iron post.											
		N. 0° 22' E., beginning new measurement.											
		Ascend 80 ft. over SW. slope.											
8.70		Spur ridge, slopes N. 60° W.; desc. 310 ft. over NW. slope.											
11.60		Dirt road, 10 lks. wide, bears E. and W.											
11.95		Dirt road, 20 lks. wide, bears N. 75° W. and S. 85° E.											