

15676

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS
19.73

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, perpetuated and recorded by Victor S. King, RLS No. 442, in 1959, and further perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with the original basalt stone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, alongside of which is an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, protruding 8 ins. above ground, from which the remains of the original bearing trees:

A decayed cedar stump, 12 ins. diam., bears
S. 45° E., 12 lks. dist., no marks visible.

and bearing trees mkd. by King

A yew, 11 ins. diam., bears S. 33° E., 52 lks.
dist., with scribe marks $\frac{1}{4}$ S14 BT visible on
open blaze.

A fir, 21 ins. diam., bears N. 41° W., 35 lks.
dist., with healed blaze.

and a bearing tree mkd. by Powell

A fir, 8 ins. diam., bears S. 59° E., 17 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 31 S R 5 W

$\frac{1}{4}$
S 15 | S 14
1972

Deposit iron pipe and corner stone alongside iron
post.

N. 2° 11' W., beginning new measurement.

Descend 325 ft. over N. slope.

11.80 Creek, 3 lks. wide, course N. 70° W.; asc. 160 ft. over
S. slope.

17.50 Spur, slopes S. 80° W.; desc. 75 ft. over N. slope.

19.78 Point for the N $\frac{1}{16}$ sec. cor. of secs. 14 and 15.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins.
in the ground, to bedrock, in a mound of stone, 2 ft.
base, to top, with brass cap mkd.

N $\frac{1}{16}$
S 15 | S 14
1973

from which

A fir, 10 ins. diam., bears N. 87° E., 33 lks.
dist., mkd. N $\frac{1}{16}$ S14 BT.

A fir, 10 ins. diam., bears S. 80° W., 39 lks.
dist., mkd. N $\frac{1}{16}$ S15 BT.

Descend 260 ft. over N. slope.