

15678

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

E 1/16 $\frac{S 11}{S 14}$
1973

from which

A fir, 23 ins. diam., bears N. 31° E., 87 lks.
dist., mkd. E 1/16 S11 BT.

A fir, 9 ins. diam., bears S. 87° W., 160 lks.
dist., mkd. E 1/16 S14 BT.

Descend 30 ft. over NW. slope.

20.70 Ravine, drains N. 5° E.; asc. 100 ft. over NE. slope.

25.50 Spur, slopes N. 5° W.; desc. 345 ft. over broken NW.
slope.

40.36 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

T 31 S R 5 W
 $\frac{1}{4}$ $\frac{S 11}{S 14}$
1973

from which

A fir, 8 ins. diam., bears N. 23° E., 49 lks.
dist., mkd. $\frac{1}{4}$ S11 BT.

A fir, 28 ins. diam., bears S. 2° W., 97 lks.
dist., mkd. $\frac{1}{4}$ S14 BT.

Descend 360 ft. over NW. slope.

52.40 Creek, 2 lks. wide, course N.; asc. 290 ft. over NE.
slope.

60.54 Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16 $\frac{S 11}{S 14}$
1973

from which

A fir, 8 ins. diam., bears S. 2½° E., 44½ lks.
dist., mkd. W 1/16 S14 BT.

A fir, 7 ins. diam., bears N. 33° W., 66 lks.
dist., mkd. W 1/16 S11 BT.

Corner is located on spur, slopes N.

Descend 265 ft. over NE. slope.