

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS 77.10	West Fork Canyon Creek, 5 lks. wide, course N. 20° E.; asc. 25 ft. over NE. slope.
79.10	Gravelled road, 40 lks. wide, bears N. 20° E. and S. 10° W.
79.90	Creek, 3 lks. wide, course S. 20° E.; asc. 20 ft. over NE. slope.
80.72	The cor. of secs. 10, 11, 14, and 15. Land, mountainous. Soil, rocky loam. Timber, fir, cedar, hemlock, madrone, pine, maple, live oak, and chinquapin; undergrowth, hazel, arrowwood, vine maple, fern, salal, rhododendron, and poison oak,
	N. 2° 39' E., bet. secs. 10 and 11. Descend 15 ft. over NE. slope.
0.70	Power transmission lines, bears N. 30° E. and S. 30° W.
0.90	Creek, 5 lks. wide, course S. 45° E.; asc. 1,065 ft. over broken S. slope.
2.00	Gravelled road, 30 lks. wide, bears N. 40° W. and S. 40° E.
39.57	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. $\frac{1}{4}$ S 10 S 11 T 31 S R 5 W 1973 from which A white oak, 16 ins. diam., bears S. 35 $\frac{1}{2}$ ° E., 81 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S11 BT. A live oak, 13 ins. diam., bears N. 44 $\frac{1}{2}$ ° W., 65 lks. dist., mkd. $\frac{1}{4}$ S10 BT. Ascend 250 ft. over broken SW. slope.
63.50	Ridge, bears N. 45° W. and S. 40° E.; desc. 400 ft. over NE. slope.
79.14	The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by Victor S. King, RLS No. 442, in 1959, monumented with an iron rod, 1 in. diam., firmly set, protruding 10 ins. above ground, from which the remains of the original bearing trees: A fir snag, 38 ins. diam., bears S. 35° E., 30 lks. dist., no marks visible. and bearing trees mkd. by King