

15682

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 31 S R 5 W

 $\frac{1}{2}$
S 3 | S 2
1973

from which

A fir, 22 ins. diam., bears N. $74\frac{1}{4}^\circ$ E., 75 lks.
dist., mkd. $\frac{1}{4}$ S2 BT.

A fir, 32 ins. diam., bears S. $73\frac{1}{4}^\circ$ W., 75 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

Ascend 30 ft. over SE. slope.

41.00 Spur, slopes N. 60° E.; desc. 425 ft. over N. slope.50.55 Creek, 2 lks. wide, course N. 80° E.; asc. 60 ft. over SF slope.57.15 Spur, slopes N. 65° E.; desc. 10 ft. over NE. slope.

57.60 Point for the N 1/16 sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

N 1/16
S 3 | S 2
1973

from which

A fir, 14 ins. diam., bears S. $55\frac{1}{4}^\circ$ E., 80 lks.
dist., mkd. N 1/16 S2 BT.

A fir, 15 ins. diam., bears S. $5\frac{3}{4}^\circ$ W., 84 lks.
dist., mkd. N 1/16 S3 BT.

Descend 350 ft. over NE. slope.

67.20 Point for the N-N 1/64 sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

N-N 1/64
S 3 | S 2
1973

from which

A fir, 22 ins. diam., bears N. $46\frac{1}{2}^\circ$ E., 46 lks.
dist., mkd. NN 1/64 S2 BT.

A fir, 10 ins. diam., bears S. $89\frac{1}{4}^\circ$ W., 53 lks.
dist., mkd. NN 1/64 S3 BT.

Descend 155 ft. over broken NE. slope.

73.35 Bottom of descent, slopes E.; asc. 65 ft. over SE. slope.

78.14 The cor. of secs. 2 and 3 only, on the N. bdy. of the Tp., hereinbefore described.