

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay loam.
Timber, cedar, hemlock, fir, madrone, pine, live oak,
maple, and dogwood; undergrowth, hazel, arrowwood, vine
maple, Oregon grape, salal, fern, rhododendron, and
poison oak.

From the cor. of secs. 22, 23, 26, and 27.

S. 88° 46' W., bet. secs. 22 and 27.

Ascend 265 ft. over E. slope, through scattering timber
and dense undergrowth.

- 10.00 Ridge, bears N. 40° E. and S. 60° W., also dirt road,
20 lks. wide, bears same; desc. 165 ft. over NW. slope.
- 18.70 Ravine, drains N. 10° E.; asc. 115 ft. over NE. slope.
- 23.60 Spur, slopes N. 15° W.; desc. 310 ft. over NW. slope.
- 33.85 Ravine, drains N. 60° W.; asc. 90 ft. over NE. slope.
- 40.63 The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, perpetuated and re-
corded by John M. Powell, Deputy County Surveyor, in
1966, monumented with an iron pipe, 1 in. diam., firmly
set, protruding 10 ins. above ground, with brass cap
mkd.

COUNTY SURVEYORS OFFICE

T 31 S
S 22
S 27
R 5 W
1966

from which the original bearing trees

A fir, 30 ins. diam., bears N. 30° E., 6 lks.
dist., with illegible scribe marks visible on
open double blaze.

A fir, 25 ins. diam., bears S. 29° W., 26 lks.
dist., with illegible scribe marks visible on
open double blaze.

Corner is located on spur, slopes N. 35° W.

S. 89° 58' W., beginning new measurement.

Descend 460 ft. over NW. slope.

- 12.35 Creek, 2 lks. wide, course N. 10° W.; asc. 160 ft. over
NE. slope.
- 18.85 Spur, slopes N. 5° W.; desc. 55 ft. over NW. slope.
- 20.55 Ravine, drains N. 10° W.; asc. 35 ft. over NE. slope.
- 22.40 Spur, slopes N. 10° E.; desc. 20 ft. over NW. slope.
- 23.70 Ravine, drains N. 45° E.; asc. 145 ft. over E. slope.