

15684

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS  
34.90

Spur, slopes N. 30° W.; desc. 165 ft. over W. slope.

40.43

The cor. of secs. 21, 22, 27, and 28, perpetuated and recorded by Victor S. King, RLS No. 442, in 1959, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

*FDOX  
By crane  
4/9/66-64  
M/11/6-64  
CS 5/1/67*

COUNTY SURVEYORS OFFICE

T 31 S R 5 W  
S 21 | S 22  
S 28 | S 27  
1966

from which the remains of the original bearing trees

A fir, 34 ins. diam., bears S. 30° E., 15 lks. dist., with healed blaze.

and bearing trees mkd. by King

A fir, 17 ins. diam., bears N. 66° E., 44 lks. dist., with healed blaze.

A grand fir, 14 ins. diam., bears S. 51° W., 29½ lks. dist., with illegible scribe marks visible on open blaze.

A grand fir, 36 ins. diam., bears N. 32° W., 82 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, madrone, live oak, pine, and chinquapin; undergrowth, hazel, salal, arrowwood, Oregon grape, fern, vine maple, and poison oak.

From the cor. of secs. 10, 11, 14, and 15.

S. 89° 19' W., bet. secs. 10 and 15.

Ascend 785 ft. over NE. slope, through moderate timber and dense undergrowth.

37.15

Spur, slopes N. 20° W.; desc. 125 ft. over NW. slope.

40.46

Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 5 W  
¼ S 10  
S 15  
1973

from which

A fir, 40 ins. diam., bears S. 42½° E., 11 lks. dist., mkd. ¼ S15 BT.

A fir, 21 ins. diam., bears N. 11° W., 59½ lks. dist., mkd. ¼ S10 BT.