

15686

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
16.10	Spur, slopes N.; desc. 170 ft. over broken NW. slope.
26.70	Creek, 2 lks. wide, course N.; asc. 10 ft. over NE. slope.
28.70	Spur, slopes N.; desc. 40 ft. over NW. slope.
31.10	Creek, 6 lks. wide, course N. 60° E.; asc. 50 ft. over SE. slope.
37.95	Dirt road, 15 lks. wide, bears N. 60° E. and W.
39.29	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, perpetuated and recorded by Victor S. King, RLS No. 442, in 1959, from original evidence no longer in existence, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 5 W

$\frac{1}{4}$ $\frac{S 9}{S 16}$

1966

from which bearing trees mkd. by King

A yew, 12 ins. diam., bears N. 74° E., 58 lks. dist., with healed blaze.

A white fir, 13 ins. diam., bears N. 64° W., 62 $\frac{1}{2}$ lks. dist., with healed blaze.

N. 89° 50' W., beginning new measurement.

Ascend 225 ft. over SE. slope.

20.60	Spur, slopes S.; asc. 105 ft. over SW. slope.
27.55	Creek, 5 lks. wide, course S. 45° E.; asc. 350 ft. over NE. slope.
37.50	Spur, slopes N.; desc. 20 ft. over NW. slope.
39.47	The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

T 31 S R 5 W

$\frac{S 8 | S 9}{S 17 | S 16}$

1966

from which the remains of the original bearing trees

A dogwood stump, 8 ins. diam., bears S. 21° E., 13 lks. dist., no marks visible.

and bearing trees mkd. by Victor S. King, RLS No. 442, in 1959

A grand fir, 26 ins. diam., bears N. 69 $\frac{1}{2}$ ° E., 13 lks. dist., with scribe marks S9 T31S R5W BT visible on open blaze.