

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

(Remonumenting a corner established by John W. McClung, Deputy Surveyor, in 1872 and reestablished by Marvin J. Lytle, Cadastral Engineer, in 1950)

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, perpetuated and recorded by David M. Thompson, Registered Land Surveyor, No. 911, in 1971, monumented with an iron rod, 24 ins. long, $\frac{3}{8}$ in. diam., firmly set 20 ins. in the ground, from which the remains of the bearing trees mkd. by Lytle in 1950:

A cedar, 54 ins. diam., bears S. 52° E., 40 lks. dist., with scribe marks $\frac{1}{4}$ S22 visible on open blaze. (Record, S. 33° E.)

A cedar snag, 14 ins. diam., bears S. 65° W., 76 lks. dist., with scribe marks $\frac{1}{4}$ S23 BT visible on open blaze. (Record, S. 15 $\frac{1}{2}$ ° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 6 W

$\frac{1}{4}$
S 22 | S 23
1972

from which new bearing trees

A cedar, 20 ins. diam., bears N. 85° E., 39 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

A twin maple, 25 ins. diam., bears S. 78° W., 38 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

Deposit the iron rod alongside the iron post.

(Remonumenting corners established by John W. McClung, Deputy Surveyor, in 1872)

The cor. of secs. 19, 20, 29, and 30, determined at record distance from the remains of the original bearing trees:

A fir snag, 20 ins. diam., bears N. 20° E., 45 lks. dist., with scribe marks BT visible on opened and decayed blaze.

A decayed fir stump, 14 ins. diam., bears S. 44° W., 26 lks. dist., with scribe marks BT visible on opened blaze. (Record, S. 18° W.)

and bearing trees mkd. and recorded by A. H. Hinkson, Deputy County Surveyor, in 1937

A fir, 52 ins. diam., bears S. 47° E., 61 lks. dist., with fragmentary scribe marks visible on opened and burned blaze.

A fir, 40 ins. diam., bears N. 41° W., 45 lks. dist., with fragmentary scribe marks visible on partially open blaze.

At the corner point