

15709

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A PORTION OF THE PRECEDING NOTES PERTAIN TO LANE COUNTY AND ARE NOT A PART OF THIS RECORDING. A FULL SET MAY BE SEEN AT THE REEDSPORT COURTHOUSE OR LANE COUNTY.

*FD 4/41
D. Rec. m/113 AS
B.C. & L BTs*

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 20 S R 6 W
S 19 | S 20
S 30 | S 29
1972

from which new bearing trees

A fir, 24 ins. diam., bears N. 57° E., 33 lks. dist., mkd. T20S R6W S20 BT.

A fir, 8 ins. diam., bears S. 19° W., 38 lks. dist., mkd. T20S R6W S30 BT.

The ¼ sec. cor. of secs. 19 and 20, monumented with the remains of the original corner tree; a decayed fir stump, 14 ins. diam., no marks visible, from which the remains of the original bearing trees:

A fir snag, 24 ins. diam., bears S. 20° E., 8 lks. dist., with scribe marks ¼ S visible on opened blaze.

A fir snag, 18 ins. diam., bears N. 73° W., 18 lks. dist., with no marks visible on opened and rotted blaze. (Record, N. 75° W.)

At the corner point

Remove the decayed fir stump: set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 20 S R 6 W
¼
S 19 | S 20
1972

from which new bearing trees

A fir, 23 ins. diam., bears S. 70° E., 110 lks. dist., mkd. ¼ S20 BT.

A fir, 25 ins. diam., bears S. 82° W., 17 lks. dist., mkd. ¼ S19 BT.

The cor. of secs. 17, 18, 19, and 20, determined at record bearing and distance from the remains of bearing trees mkd. and recorded by R. N. Hinkson, Deputy County Surveyor, in 1942, from original evidence no longer in existence:

A fir, 28 ins. diam., bears N. 38° E., 38 lks. dist., with healed double blaze.

A sawed fir stump, 36 ins. diam., bears N. 70° W., 47 lks. dist., with scribe marks 6 S18 CS visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.