

15712

Dependent Resurvey of a Portion of the West Boundary,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

DOUGLAS COUNTY SURVEYORS OFFICE

	R	T 27 S	R	
Coos	9	25 30	8	Douglas
Co.	W	36 31	W	Co.
		1957		

from which the remains of the original bearing trees

A sawed fir stump, 52 ins. diam., bears N. 33½° E.,
32 lks. dist., no marks visible.

A sawed cedar stump, 32 ins. diam., bears
N. 20° W., 41 lks. dist., with scribe marks
T27S R9W S25 DCS BT visible on open blaze.
This tree was rescribed by Byron.

and a bearing tree mkd. by Byron

A sawed cedar stump, 52 ins. diam., bears
S. 33° W., 80 lks. dist., with scribe marks
T27S R9W S36 DCS BT visible on open blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 3½° E., 15 lks.
dist., mkd. T27S R8W S30 BT.

A fir, 8 ins. diam., bears S. 66½° W., 68½ lks.
dist., mkd. T27S R9W S36 BT.

A fir, 8 ins. diam., bears N. 49¾° W., 86 lks.
dist., mkd. T27S R9W S25 BT.

No suitable tree available in sec. 31.

N. 0° 07' W., along the W. bdy. of sec. 30, marking and
blazing the true line.

Descend 385 ft. over N. slope, through clear-cut area
and dense undergrowth.

3.25 Burnt Mountain Ridge Road, asphalt surfaced, 25 lks.
wide, bears N. 35° W. and S. 20° E., in curve.

4.50 Slope changes to NE., thence over broken NE. slope.

27.60 Creek, 25 lks. wide, course S. 30° E.; asc. 160 ft.
over SW. slope.

34.15 Spur, slopes N. 70° W.; desc. 50 ft. over NW. slope,
also edge of timber, bears N. and E., thence along west
edge of timber.

38.65 Creek, 6 lks. wide, course S. 40° W.; asc. 30 ft. over
SE. slope.

39.86 Point for the ¼ sec. cor. of sec. 25 only, T. 27 S.,
R. 9 W., at midpoint latitudinally on the E. bdy. of
the sec.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

	T 27 S	
	R 9 W R 8 W	
¼ S 25		
	1976	