

15713

Dependent Resurvey of a Portion of the West Boundary,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 3 ins. diam., bears S. $27\frac{3}{4}^{\circ}$ W., 125 lks.
dist., mkd. X BT.

A fir, 3 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., $39\frac{1}{2}$ lks.
dist., mkd. X BT.

Ascend 30 ft. over SE. slope.

40.95 The $\frac{1}{4}$ sec. cor. of sec. 30 only, perpetuated and recorded by Robert C. Adamek, RLS No. 0999, for Weyerhaeuser Timber Company, in 1975, monumented with an iron pipe, $\frac{3}{8}$ in. diam., firmly set, projecting 6 ins. above ground, and in the root hole of the original corner tree, a hemlock, 36 ins. diam., lying downhill, no marks visible on healed blaze, from which the remains of the original bearing trees:

A yew, 17 ins. diam., bears N. 50° E., 30 lks.
dist., with axe marks visible on open blaze.

and the remains of bearing trees mkd. by Adamek

A hemlock, 12 ins. diam., bears S. 10° E., 34
lks. dist., mkd. $\frac{1}{4}$ S30 BT.

A sawed fir stump, 40 ins. diam., bears N. 11° W.,
 $42\frac{1}{2}$ lks. dist., with a galvanized nail with "W"
embossed on head, at base.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, over the iron pipe, with brass cap mkd.

T 27 S
R 9 W | R 8 W
 | $\frac{1}{4}$ S 30
 1976

N. $0^{\circ} 03'$ W., beginning new measurement.

Ascend 475 ft. over S. slope.

22.20 Corner of timber, edges bear S. and S.; enter heavy
timber and moderate undergrowth.

26.93 An original line tree in good condition, a fir, 90 ins.
diam., mkd. with 2 notches on N. and S. sides. This
now becomes an angle point.

from which

A hemlock, 16 ins. diam., bears N. 18° E., 46 lks.
dist., mkd. AP S30 BT.

A yew, 16 ins. diam., bears N. 55° W., $11\frac{1}{2}$ lks.
dist., mkd. AP S25 BT.

N. $1^{\circ} 00'$ W., beginning new measurement.

Ascend 375 ft. over S. slope.