

370

15714

Dependent Resurvey of a Portion of the West Boundary,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

| | | | | | | | | | | | | | |
|--------|---|--------|--------|-------|-------|------|--------|--|------|--|-------|--|------|
| CHAINS | | | | | | | | | | | | | |
| 11.84 | Point for the closing cor. of secs. 24 and 25, T. 27 S., R. 9 W., hereinafter described. | | | | | | | | | | | | |
| | Ascend 10 ft. over S. slope. | | | | | | | | | | | | |
| 12.45 | Dirt road, 20 lks. wide, bears E. and W., also corner of timber, edges bear N. and E.; thence along east edge of timber. | | | | | | | | | | | | |
| 13.38 | Point for the cor. of secs. 19 and 30 only, at proportionate distance; there is no remaining evidence of the original corner. | | | | | | | | | | | | |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 S</td><td>T 27 S</td></tr> <tr><td>R 9 W</td><td></td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td></td><td>S 30</td></tr> <tr><td></td><td>R 8 W</td></tr> <tr><td></td><td>1976</td></tr> </table> | T 27 S | T 27 S | R 9 W | | S 24 | S 19 | | S 30 | | R 8 W | | 1976 |
| T 27 S | T 27 S | | | | | | | | | | | | |
| R 9 W | | | | | | | | | | | | | |
| S 24 | S 19 | | | | | | | | | | | | |
| | S 30 | | | | | | | | | | | | |
| | R 8 W | | | | | | | | | | | | |
| | 1976 | | | | | | | | | | | | |
| | No suitable trees available within limits. | | | | | | | | | | | | |
| | Set a 5 ft. steel fence post alongside iron post. | | | | | | | | | | | | |
| | Corner is located on ridge, bears N. 80° W. and S. 80° E. | | | | | | | | | | | | |
| | Land, mountainous. | | | | | | | | | | | | |
| | Soil, rocky clay loam. | | | | | | | | | | | | |
| | Timber, fir, hemlock, cedar, yew, and chinquapin; undergrowth, vine maple, rhododendron, sword fern, and hazel. | | | | | | | | | | | | |
| | <p>N. 1° 00' W., along the W. bdy. of sec. 19.</p> <p>Descend 675 ft. over broken NE. slope.</p> | | | | | | | | | | | | |
| 18.90 | Corner of timber, bears S. and E.; enter heavy timber and moderate undergrowth. | | | | | | | | | | | | |
| 40.24 | The ¼ sec. cor. of sec. 19 only, perpetuated and recorded by Robert C. Adamek, RLS No. 0999, for Weyerhaeuser Timber Company, in 1975 monumented with an iron pipe, ¾ in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees: | | | | | | | | | | | | |
| | <p>A yew, 12 ins. diam., bears N. 70½° W., 56 lks. dist., with scribe marks ½ S visible on open blaze. (Record, hemlock)</p> | | | | | | | | | | | | |
| | and a bearing tree mkd. by Adamek | | | | | | | | | | | | |
| | <p>A hemlock, 8 ins. diam., bears N. 13½° W., 67½ lks. dist., with a galvanized nail with "W" embossed on head, at base.</p> | | | | | | | | | | | | |
| | At the corner point | | | | | | | | | | | | |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, over the iron pipe, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd. | | | | | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 S</td><td></td></tr> <tr><td>R 9 W</td><td>R 8 W</td></tr> <tr><td></td><td>¼ S 19</td></tr> <tr><td></td><td>1976</td></tr> </table> | T 27 S | | R 9 W | R 8 W | | ¼ S 19 | | 1976 | | | | |
| T 27 S | | | | | | | | | | | | | |
| R 9 W | R 8 W | | | | | | | | | | | | |
| | ¼ S 19 | | | | | | | | | | | | |
| | 1976 | | | | | | | | | | | | |