

Dependent Resurvey of a Portion of the West Boundary,  
T. 27 S., R. 8 W., Willamette Meridian, Oregon

## CHAINS

from which new bearing trees

A hemlock, 6 ins. diam., bears N.  $10\frac{1}{2}^{\circ}$  E., 125 lks.  
dist., mkd.  $\frac{1}{4}$  S19 BT.

A hemlock, 9 ins. diam., bears S.  $19\frac{3}{4}^{\circ}$  E., 119 lks.  
dist., mkd.  $\frac{1}{4}$  S19 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, yew, and chinquapin; under-  
growth, vine maple, rhododendron, sword fern, and hazel.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 27 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel W. Lackland,  
U. S. Deputy Surveyor, in 1897)

From the cor. of secs. 23, 24, 25, and 26, determined at  
record bearing and distance from the remains of the  
original bearing trees:

A fir snag, 48 ins. diam., bears N.  $22^{\circ}$  E., 34 lks.  
dist., with healed blaze.

A root hole, bears S.  $65^{\circ}$  E., 21 lks. dist., with  
a down fir alongside, 25 ins. diam., no marks  
visible.

A cedar, 11 ins. diam., bears S.  $16\frac{1}{2}^{\circ}$  W., 41 lks.  
dist., with healed blaze.

A root hole, bears N.  $74^{\circ}$  W., 5 lks. dist., with  
a down fir alongside, 17 ins. diam., with healed  
blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 27	S R 9 W
S 23	S 24
S 26	S 25
1976	

from which new bearing trees

A yew, 6 ins. diam., bears N.  $44^{\circ}$  E., 39 lks.  
dist., mkd. T27S R9W S24 BT.

A hemlock, 8 ins. diam., bears S.  $18\frac{1}{2}^{\circ}$  E., 27  
lks. dist., mkd. T27S R9W S25 BT.

A yew, 9 ins. diam., bears N.  $74\frac{3}{4}^{\circ}$  W., 49 lks.  
dist., mkd. T27S R9W S23 BT.

N.  $88^{\circ} 47'$  E., bet. secs. 24 and 25, marking and blazing  
the true line.

Ascend 110 ft. over SW. slope, through heavy timber and  
moderate undergrowth.