

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 26 S R 2 W
S 23 | S 24
S 26 | S 25
1916

from which the remains of the original bearing trees

A fir, 46 ins. diam., bears N. 53° E., 40 lks. dist., with scribe marks T26S R2W S24 CS visible on bark. This tree was rescribed by Vernon Tracy, Deputy County Surveyor, in 1967. (Record, N. 50° E.)

A chinquapin snag, 10 ins. diam., bears N. 14° W., 21 lks. dist., with scribe marks 6 W 23 visible on open blaze. (Record, N. 20° W.)

and the remains of bearing trees mkd. by Tracy

A cedar, 20 ins. diam., bears S. 6½° E., 138 lks. dist., with scribe marks T26S R2W S26 CS BT visible on open blaze.

A pine snag, 9 ins. diam., bears N. 52½° W., 12 lks. dist., with scribe marks T26S R2W S23 CS BT visible on open blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 80° W., 96 lks. dist., mkd. T26S R2W S23 BT.

N. 0° 36' E., bet. secs. 23 and 24, marking and blazing the true line.

Descend 70 ft. over NE. slope, through dense undergrowth.

6.20 Rock bluff, 60 ft. high, bears E. and W.; desc. 850 ft. over NE. slope.

11.20 Gravelled road, 15 lks. wide, bears N. 30° W. and S. 30° E.

42.86 The ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

S 23 | S 24
¼ S
1916

from which the original bearing trees

A fir, 51 ins. diam., bears N. 47° E., 6 lks. dist., with healed blaze. (Record, N. 50° E.)

A maple, 13 ins. diam., bears S. 38° W., 31½ lks. dist., with scribe marks S23 BT visible on open decayed blaze. (Record, 30 lks.)

and bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1967

A cedar, 10 ins. diam., bears S. 2° E., 46 lks. dist., with scribe marks ¼ S24 CS BT visible on open double blaze.