

15721

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 10 ins. diam., bears N. $64\frac{1}{2}^\circ$ W., 41 lks. dist., with scribe marks $\frac{1}{4}$ S23 CS BT visible on open double blaze.

N. $1^\circ 52'$ E., beginning new measurement.

Descend 200 ft. over NE. slope.

- 9.00 Rock bluff, 100 ft. high, bears E. and W.; desc. 245 ft. over N. slope.
- 15.05 Left bank of North Umpqua River, course W.
- 20.40 Right bank of North Umpqua River, course W.; asc. 60 ft. over S. slope, through Susan Creek State Park.
- 31.90 Leave Susan Creek State Park, edge bears N. 60° W. and S. 60° E.
- 32.30 State Highway No. 138, 60 lks. wide, bears N. 60° W. and S. 60° E.
- 41.80 Gravelled road, 20 lks. wide, bears N. 80° W. and S. 80° E.
- 42.82 The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, alongside of which is a basalt stone, 10 x 10 x 6 ins. The brass cap is mkd.

COUNTY SURVEYORS OFFICE

T 26 S R 2 W

S 14 | S 13

S 23 | S 24

1961

from which the remains of the original bearing trees

A sawed and decayed fir stump, 30 ins. diam., bears N. 25° E., 68 lks. dist., no marks visible.

A fir, 35 ins. diam., bears S. 20° E., 29 lks. dist., with healed blaze.

and bearing trees mkd. by Godfrey

A white oak, 10 ins. diam., bears S. 70° E., $33\frac{1}{2}$ lks. dist., with healed double blaze.

A fir, 17 ins. diam., bears S. 81° W., 53 lks. dist., with healed double blaze.

A white oak, 7 ins. diam., bears N. $86\frac{1}{2}^\circ$ W., 37 lks. dist., with healed double blaze.

and a new bearing tree

A cedar, 5 ins. diam., bears N. 66° E., $49\frac{1}{2}$ lks. dist., mkd. X BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, maple, madrone, pine, alder, and chinquapin; undergrowth, salal, hazel, poison oak, Oregon grape, young timber, arrowwood, and fern.