

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

- From the cor. of secs. 23, 24, 25, and 26.
S. 86° 35' W., bet. secs. 23 and 26.
Ascend 60 ft. over NE. slope, through scattered timber and dense undergrowth.
- 0.40 Abandoned dirt road, 15 lks. wide, bears N. 25° E., to landing, and S. 40° W.
- 8.00 Spur, slopes N.; desc. 85 ft. over NW. slope.
- 23.25 Creek, 3 lks. wide, course N. 25° W.; asc. 55 ft. along broken N. slope.
- 31.10 Enter timber, edge bears N. and S.
- 31.20 Spur, slopes N.; desc. 55 ft. over NW. slope.
- 35.00 Rock bluff, 90 ft. high, bears NE. and SW.; desc. 240 ft. over NW. slope.
- 40.44 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

S 23
 $\frac{1}{4}$
S 26
1918

from which the remains of bearing trees mkd. by Mensch

A decayed cedar stump, size indeterminate, bears S. 25° E., 5 lks. dist., no marks visible.

and bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1967

A cedar, 28 ins. diam., bears N. 23° W., 87 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S23 CS BT visible on open double blaze.

A cedar, 39 ins. diam., bears S. 85° E., 178 lks. dist., with scribe marks $\frac{1}{4}$ S26 CS BT visible on open double blaze.

- S. 86° 24' W., beginning new measurement.
Descend 520 ft. over NW. slope.
- 9.50 Dirt road, 15 lks. wide, bears NE. and SW.
- 17.20 Creek, 5 lks. wide, course N. 40° W.; asc. 400 ft. over broken NE. slope.
- 29.30 Dirt road, 15 lks. wide, bears NW. and SE.
- 36.00 Top of ascent, slopes N.; desc. 10 ft. over gentle W. slope.
- 40.30 The cor. of secs. 23 and 26 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.