

15723

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 26 S
| S 23
| S 26
R 2 W
1918

from which the remains of the original bearing trees

A fir snag, 20 ins. diam., bears N. 43° E., 11 lks. dist., with healed blaze.

and bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1967

A white fir, 8 ins. diam., bears N. 55° E., 21 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A hemlock, 10 ins. diam., bears S. 38° E., 5 lks. dist., with scribe marks T26S R2W S26 CS BT visible on open double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, hemlock, cedar, maple, madrone, and alder; undergrowth, salal, Oregon grape, hazel, arrowwood, young timber, and fern.

N. 1° 24' E., on the W. bdy. of sec. 23.

Descend 640 ft. over NE. slope, through light timber and dense undergrowth.

8.99 From this point, the closing cor. of secs. 22 and 27, perpetuated by person(s) unknown, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 10 ins. above ground, bears West, 0.044 chs. dist., from which the remains of the original bearing trees:

A hemlock snag, 14 ins. diam., bears S. 49° W., 54 lks. dist., with scribe marks CC T26S R2W S27 BT visible on open blaze.

A sawed fir stump, 44 ins. diam., bears N. 20° W., 16 lks. dist., with healed blaze.

9.45 Gravelled road, 15 lks. wide, bears S. 85° E. and S. 80° W.

28.45 Creek, 3 lks. wide, course N. 75° E.; asc. 15 ft. over SE. slope.

30.35 Spur, slopes N. 60° E.; desc. 190 ft. over NE. slope.

42.61 The 1/4 sec. cor. of sec. 23 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, alongside of which is the granite stone, 16 x 10 x 5 ins., set by William N. Gibb, in 1909, mkd. 1/4 on W. face. The brass cap is mkd.

FD. OK 2/2004
D. EDWARDS
M 143-66

S 22 | S 23
1/4 S | 1/4
1918

from which the remains of the original bearing trees