

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A maple, 21 ins. diam., bears N. 89° W., 11 lks. dist., with healed blaze.

and a bearing tree mkd. by Mensch

A hemlock, 18 ins. diam., bears S. 21° E., 44 lks. dist., with healed blaze. (Record, S. 15° E.)

N. 0° 12' E., beginning new measurement.

Descend 140 ft. over NE. slope.

10.20 Creek, 2 lks. wide, course N. 25° E.; desc. 10 ft. over NE. slope.

12.30 Creek, 10 lks. wide, course N. 20° W.; desc. 80 ft. over general N. slope.

23.18 Point for the N 1/16 sec. cor. of sec. 23 only, on the W. bdy. of sec. 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

N 1/16  
S 23  
1975

from which

A cedar, 10 ins. diam., bears N. 80° E., 49 lks. dist., mkd. N 1/16 S23 BT.

A fir, 13 ins. diam., bears S. 52° E., 33½ lks. dist., mkd. N 1/16 S23 BT.

Descend 65 ft. over N. slope.

25.10 Left bank of North Umpqua River, course W.

30.40 Right bank of North Umpqua River, course W.; asc. 160 ft. over SE. slope.

34.20 State Highway No. 138, 60 lks. wide, bears E. and W.

46.36 The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by James W. Byron, County Surveyor, in 1957, monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, alongside of which the basalt stone, 18 x 6 x 6 ins., set by William N. Gibb, in 1909, mkd. with 3 notches on S. and 2 notches on E. edges. The brass cap is mkd.

COUNTY SURVEYORS OFFICE  
T 26 S R 2 W  
SEC 15 | 14  
22 | 23  
1957

*FD. CAP 4 BTs  
4/13/92 - BLM  
C.S. 63/140*

from which the remains of the original bearing trees

A fir, 25 ins. diam., bears S. 71½° W., 52½ lks. dist., with healed blaze.

and bearing trees mkd. by Mensch