

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which new bearing trees</p> <p>A fir, 13 ins. diam., bears N. 4° W., 57 lks. dist., mkd. ½ S14 BT.</p> <p>A fir, 14 ins. diam., bears S. 56° W., 97½ lks. dist., mkd. ½ S23 BT.</p> <hr/> <p>S. 89° 47' W., beginning new measurement.</p> <p>Descend 25 ft. over nearly level land.</p>
2.95	Abandoned dirt road, 15 lks. wide, bears NE. and SW.
13.70	Susan Creek Trail, 5 lks. wide, bears N. 50° W. and S. 50° E.
17.60	Dirt road, 10 lks. wide, bears N. 5° W. and S. 5° E.
19.05	Susan Creek, 40 lks. wide, course S. 30° E.; asc. 5 ft. over nearly level land.
19.87	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} W\ 1/16\ \frac{S\ 14}{S\ 23} \\ 1975 \end{array}</math> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears N. 35° W., 10 lks. dist., mkd. W 1/16 S14 BT.</p> <p>A fir, 16 ins. diam., bears S. 17° E., 16 lks. dist., mkd. W 1/16 S23 BT.</p> <p>Continue over nearly level land.</p>
23.45	Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.; asc. 90 ft. over SE. slope.
31.15	The northern most corner of a wood frame building, 32 x 26 ft., the long side of which bears S. 60° W.
39.74	The cor. of secs. 14, 15, 22, and 23.
	<p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, yew, maple, alder, and madrone; undergrowth, poison oak, Oregon grape, salal, and fern.</p> <hr/> <p style="text-align: center;">Subdivision of Section 23, T. 26 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 23 and 26.</p> <p>N. 0° 30' E., on the N. and S. center line of sec. 23.</p> <p>Descend 570 ft. over NW. slope, through medium timber and dense undergrowth.</p>