

15727

Subdivision of Section 23, T. 26 S., R. 2 W.,
Willamette Meridian, Oregon

CHAINS 5.55	Gravelled road, 15 lks. wide, bears N. 85° W. and S. 75° E.
18.10	Gravelled road, 15 lks. wide, bears N. 65° W. and S. 65° E.
30.35	Enter heavy timber, edge bears E. and W., slope changes to N.
42.61	Point for the center $\frac{1}{4}$ sec. cor. of sec. 23, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 26 S R 2 W C $\frac{1}{4}$ S 23 1975 from which A cedar, 14 ins. diam., bears N. 34° E., 12 lks. dist., mkd. C $\frac{1}{4}$ S23 BT. A cedar, 13 ins. diam., bears S. 11° E., 17 lks. dist., mkd. C $\frac{1}{4}$ S23 BT. Descend 490 ft. over N. slope.
64.54	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 23. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C N $\frac{1}{16}$ S 23 C 1975 from which A hemlock, 15 ins. diam., bears N. 47° E., $22\frac{1}{2}$ lks. dist., mkd. CN $\frac{1}{16}$ S23 BT. A fir, 13 ins. diam., bears S. 55° W., 31 lks. dist., mkd. CN $\frac{1}{16}$ S23 BT. Descend 50 ft. over N. slope.
76.55	Left bank of North Umpqua River, course S. 50° W.
80.85	Right bank of North Umpqua River, course S. 50° W.; asc. 60 ft. over S. slope, also enter Susan Creek State Park.
84.80	Leave Susan Creek State Park.
85.10	State Highway No. 138, 60 lks. wide, bears N. 80° E. and S. 80° W.
86.47	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23. From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24. S. 86° 15' W., on the E. and W. center line of sec. 23. Ascend 230 ft. over NE. slope.